

 自動ドアセンサー かんたん機能比較表		赤外線センサー						ワイヤレス タッチスイッチ	サポートセンサー					非接触スイッチ				フットスイッチ			オプション		
		HA-T520	HA-T401	HA-400	HA-430	HA-260	H-17	HW-500T /500S	HZ-C	P-2109T/2209T P-2108/2208	P-2101R	P-06	P-15	DHS-1	PF-R5	PF-R1	PF-U2	PF-01S PF-01D	PF-03S	PF-05	SC-10	HK-2	
取付位置		無目内蔵型		無目取付型		無目下取付型	天井取付型	高所取付型	扉・壁	方立・壁					壁								
検出方式	赤外線	●	●	●	●	●	●																
	超音波								●														
	無線スイッチ							●															
	光電センサー									●	●	●	●		●	●	●	●	●	●			
	レーダー													●							●	●	
	その他(制御機)																						
機能	ドアウェイ監視	●	●	●	●	●																	
	高密度エリア	●	●	●	●	●																	
	ワイドエリア	●	●	●	●	●																	
	高所 (取付高さ)	● (2.0~4.0m)	● (2.0~4.0m)	● (2.0~4.0m)	● (2.0~4.0m)	● (2.0~4.0m)	● (3.0~6.0m)																
	静止体検知	●	●	●	●	●	●	●	●	●	●	●		●	●	●	●	●	●	●			
	フルカラーLED	●	●	●	●	●																	
	フラット (天井露出厚み)	● (1.5mm)				● (6.0mm)																	
	ecoモード	●	●	●	●	●																	
	雪虫モード	●	●	●	●	●	●																
	自己診断	●	●	●	●	●	●		●	●	●	●		●	●	●	●	●	●	●		● ※1	
	防水						● ※2							● ※4	● ※3								
反射・透過	反射									●	●			●	●	●							
	透過									●		●					●	●	●				
用途	起動+安全	● ※5	● ※5	● ※5	● ※5	● ※5				●													
	起動						●	●			●		●	●	●	●	●	●	●				
	安全								●	●	●		●										
設置場所	大型商業施設	●	●	●	●	●			●	●												●	
	小規模店舗	●	●	●	●	●	●		●	●	●									●	●		
	交通施設・高速道路SA/PA	●	●						●													●	
	医療施設	●	●	●	●	●			●	●			●	●	●	●	●	●	●			●	
	公共施設・鑑賞施設	●	●	●	●	●	●		●	●												●	
	外食施設・レジャー施設	●	●	●	●	●	●		●	●	●		●	●		●	●	●	●			●	
	工場・環境施設	●	●	●		●	●		●	●		●	●	●	●	●	●	●	●			●	
オフィスビル・マンション・ホテル	●	●			●	●		●	●	●	●	●	●	●	●	●	●	●				●	

※ 1 : 自己診断機能を切ることはできません。

※ 2 : 保護等級 IPX5

※ 3 : 保護等級 IP55(ロックアウト未使用時)

※ 4 : IP55相当(壁面(裏面)は該当せず)

※ 5 : 1列目の検知エリアをドアウェイに設定した場合に「安全」設定になります。ドアウェイだけの設定はありません。

※ 6 : 6色展開 (S) シルバー/ (B) ブロンズ/ (W) ホワイト/ (M) ミラー/ (G) ブラック/ (C) ステンカラー)です。