

 自动门感应器性能比较表		平移自动门					90度开闭门		工业用门
		主动及安全复合型					防夹安全开闭型		主动及安全复合型
		3H-CH01	3H-IR14	HR100-CT	HR100	SSR-3	HR400	HTP-20	SSS-5
检出方式	红外线	●	●	●	●	●		●	●
	超音波								
	无线开关								
	光电						●		
	雷达				●				
功能	门扇路径的监控			●		●			●
	高密度检知范围							●	●
	广域								●
	高位置						4.0m (13.12ft) Max		4.7m (15.42ft) Max
	静止物体检知	●	●	●	●	●	●	●	●
	全彩LED		●	●		●			●
	平整			●	●				
	ECO模式			●		●			●
	降雪模式	●	●	●	●	●	●		●
	自我诊断	●	●	●		●	●	●	●
	防水			●	●	●	●	●	●
	方向检知			●		●			●
	反射·透过	反射						●	
透过							●		
用途	起动+安全	●	●	●	●	●			●
	起动								
	安全						●	●	
安装场所	大型商业设施			●	●	●		●	
	小型商场	●	●	●	●	●	●		
	交通设施		●	●	●	●		●	
	医疗设施		●	●	●	●	●		
	公共设施		●	●	●	●			
	环境设施							●	●
	教育机构						●		
	餐饮服务设施	●	●	●	●	●	●		
	工厂设施							●	●
	艺文设施		●	●	●	●	●		
	办公大楼	●	●	●	●	●	●		●
	休闲设施		●	●	●	●	●		●
住宅		●	●	●	●	●			